

Revive Series

CLAD CASEMENT

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Operating Casement					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
Revive Clad	Casement Crank-Out	Standard	36" x 72"	LC-PG30-C	0.06
Revive Clad	Casement Crank-Out	Standard	42" x 60"	LC-PG40-C	0.01
Revive Clad	Casement Crank-Out	Standard	28" x 84"	R-PG30-C	0.07

Fixed Casement (Stationary, Picture, Transom)					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
Revive Clad	Casement Fixed	Standard	72" x 84"	LC-PG45-FW	0.02

Notes:

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum Frame Width	Minimum Frame Height	Maximum Frame Width	Maximum Frame Height
Operating			
1-4	1-6	3-6*	7-0**
Stationary / Picture / Transom			
1-6	1-0	6-0	7-0

*Up to 5'-0" frame height

**Up to 2'-4" frame width