

Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Oppg. Clad
Rough Oppg.
Frame
* Glass


4-0 3/4

4-0 3/4

4-0


14

6-8
6-8
6-7 1/2
63 7/8




4068
BI-HINGE ONLY

6-10 7/8
6-10 7/8
6-10 3/8
66 3/4




40610
BI-HINGE ONLY

7-11 7/8
7-11 7/8
7-11 3/8
79 3/4




4080
BI-HINGE ONLY

8-11 7/8
8-11 7/8
8-11 3/8
91 3/4




4090
BI-HINGE ONLY

9-11 7/8
9-11 7/8
9-11 3/8
103 3/4




40100
BI-HINGE ONLY

OTHER GRILLE PATTERNS



PRAIRIE DIAMOND SINGLE PLAZA DOUBLE PLAZA TRIPLE PLAZA

OTHER PANEL OPTIONS



1/2 LITE PANEL 3/4 LITE PANEL 1/2 LITE DIVIDED PANEL 3/4 LITE DIVIDED PANEL

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 1 3/8" FROM FRAME & ROUGH OPENING HEIGHTS.

* BOTTOM RAIL
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ▣ ADD 2 13/16" TO FRAME WIDTH
- ▣ ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ▣ ADD 6 1/2" TO FRAME WIDTH
- ▣ ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opng. Clad
Rough Opng.
Frame
* Glass


	2-7	5-0 13/16	7-6 5/8	7-11 15/16	9-0 7/16	10-0 7/16
	2-7	5-0 13/16	7-6 5/8	7-11 15/16	9-0 7/16	10-0 7/16
	2-6 1/4	5-0 1/16	7-5 7/8	7-11 3/16	8-11 11/16	9-11 11/16
	20	20	20	11 1/2 - 20 - 11 1/2	14 - 20 - 14	20
6-8 6-8 6-7 1/2 63 7/8						
	2668	5068	7668	16-50-1668	20-50-2068	26-50-2668
6-10 7/8 6-10 7/8 6-10 3/8 66 3/4						
	26610	50610	76610	16-50-16610	20-50-20610	26-50-26610
7-11 7/8 7-11 7/8 7-11 3/8 79 3/4						
	2680	5080	7680			
8-11 7/8 8-11 7/8 8-11 3/8 91 3/4						
	2690	5090				
9-11 7/8 9-11 7/8 9-11 3/8 103 3/4						
	26100	50100				

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 1 3/8" FROM FRAME & ROUGH OPENING HEIGHTS.

* BOTTOM RAIL
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

OTHER GRILLE PATTERNS




UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
 ADD 2 13/16" TO FRAME WIDTH
 ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG
 ADD 6 1/2" TO FRAME WIDTH
 ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

OTHER PANEL OPTIONS



NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series






CLAD PATIO DOOR - FRENCH INSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opq. Clad
Rough Opq.
Frame
*Glass

2-9	5-4 13/16	8-0 5/8	7-11 15/16
2-9	5-4 13/16	8-0 5/8	7-11 15/16
2-8 1/4	5-4 1/16	7-11 7/8	7-11 3/16
22	22	22	9 1/2 - 22 - 9 1/2




NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 1 3/8" FROM FRAME & ROUGH OPENING HEIGHTS.

* BOTTOM RAIL
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

OTHER GRILLE PATTERNS



UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD


- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

OTHER PANEL OPTIONS



NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opp. Clad
Rough Opng.
Frame
*Glass


	3-1	6-0 13/16	9-0 5/8	8-3 15/16	8-7 15/16
	3-1	6-0 13/16	9-0 5/8	8-3 15/16	8-7 15/16
	3-0 1/4	6-0 1/16	8-11 7/8	8-3 3/16	8-7 3/16
	26	26	26	7 1/2 - 26 - 7 1/2	9 1/2 - 26 - 9 1/2
6-8					
	3068	6068	9068	12-60-1268	14-60-1468
6-8					
	30610	60610	90610	12-60-12610	14-60-14610
6-7 1/2					
	3080	6080	9080	12-60-1280	14-60-1480
63 7/8					
	3090	6090			
6-10 7/8					
	30100	60100			
6-10 7/8					
6-10 3/8					
66 3/4					
7-11 7/8					
7-11 7/8					
7-11 3/8					
79 3/4					
8-11 7/8					
8-11 7/8					
8-11 3/8					
91 3/4					
9-11 7/8					
9-11 7/8					
9-11 3/8					
103 3/4					

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 1 3/8" FROM FRAME & ROUGH OPENING HEIGHTS.

* BOTTOM RAIL
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT


OTHER GRILLE PATTERNS



UNIT SIZE INFORMATION

- FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
 - ADD 1 13/32" TO FRAME HEIGHT
- FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
 - ADD 3 1/4" TO FRAME HEIGHT

OTHER PANEL OPTIONS



NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opp. Clad
Rough Opg.
Frame
*Glass

6-8
6-8
6-7 1/2
63 7/8

6-10 7/8
6-10 7/8
6-10 3/8
66 3/4


7-11 7/8
7-11 7/8
7-11 3/8
79 3/4

8-11 15/16
8-11 15/16
8-11 3/16
11 1/2 - 26 - 11 1/2


10-0 7/16
10-0 7/16
9-11 11/16
14 - 26 - 14

11-0 7/16
11-0 7/16
10-11 11/16
20 - 26 - 20


11-4 7/16
11-4 7/16
11-3 11/16
22 - 26 - 22




16-60-1668




20-60-2068




26-60-2668




28-60-2868




16-60-16610




20-60-20610




26-60-26610




28-60-28610




16-60-1680



20-60-2080



26-60-2680



28-60-2880

* **BOTTOM RAIL**
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 1 3/8" FROM FRAME & ROUGH OPENING HEIGHTS.

OTHER GRILLE PATTERNS




PRAIRIE




DIAMOND



SINGLE PLAZA



DOUBLE PLAZA



TRIPLE PLAZA


UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
 ADD 2 13/16" TO FRAME WIDTH
 ADD 1 13/32" TO FRAME HEIGHT


FOR CLAD WILLIAMSBURG
 ADD 6 1/2" TO FRAME WIDTH
 ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING


OTHER PANEL OPTIONS




1/2 LITE
PANEL



3/4 LITE
PANEL



1/2 LITE
DIVIDED PANEL



3/4 LITE
DIVIDED PANEL

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING


ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opg. Clad
Rough Opg.
Frame
* Glass


12-0 7/16
12-0 7/16
11-11 11/16
26

6-8
6-8
6-7 1/2
63 7/8




30-60-3068

6-10 7/8
6-10 7/8
6-10 3/8
66 3/4



30-60-30610

7-11 7/8
7-11 7/8
7-11 3/8
79 3/4



30-60-3080

*** BOTTOM RAIL**

FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

NOTE:


THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 1 3/8" FROM FRAME & ROUGH OPENING HEIGHTS.

OTHER GRILLE PATTERNS




PRAIRIE



DIAMOND



SINGLE PLAZA



DOUBLE PLAZA



TRIPLE PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ▣ ADD 2 13/16" TO FRAME WIDTH
- ▣ ADD 1 13/32" TO FRAME HEIGHT


FOR CLAD WILLIAMSBURG

- ▣ ADD 6 1/2" TO FRAME WIDTH
- ▣ ADD 3 1/4" TO FRAME HEIGHT


NOTE:

ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING


OTHER PANEL OPTIONS




1/2 LITE PANEL



3/4 LITE PANEL



1/2 DIVIDED PANEL



3/4 DIVIDED PANEL

NOTES:

CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opp. Clad
Rough Opp.
Frame
* Glass

3-2 1/2	6-3 13/16	8-6 15/16	8-10 15/16	9-2 15/16
3-2 1/2	6-3 13/16	8-6 15/16	8-10 15/16	9-2 15/16
3-1 3/4	6-3 1/16	8-6 3/16	8-10 3/16	9-2 3/16
27 1/2	27 1/2	7 1/2 - 27 1/2 - 7 1/2	9 1/2 - 27 1/2 - 9 1/2	11 1/2 - 27 1/2 - 11 1/2

6-8 6-8 6-7 1/2 63 7/8					
3268	6468	12-64-1268	14-64-1468	16-64-1668	
6-10 7/8 6-10 7/8 6-10 3/8 66 3/4					
32610	64610	12-64-12610	14-64-14610	16-64-16610	
7-11 7/8 7-11 7/8 7-11 3/8 79 3/4					
3280	6480	12-64-1280	14-64-1480	16-64-1680	
8-11 7/8 8-11 7/8 8-11 3/8 91 3/4			<div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center;">UNIT SIZE INFORMATION</p> <p>FOR CLAD BRICKMOULD</p> <ul style="list-style-type: none"> □ ADD 2 13/16" TO FRAME WIDTH □ ADD 1 13/32" TO FRAME HEIGHT <p>FOR CLAD WILLIAMSBURG</p> <ul style="list-style-type: none"> □ ADD 6 1/2" TO FRAME WIDTH □ ADD 3 1/4" TO FRAME HEIGHT </div>		
3290	6490				
9-11 7/8 9-11 7/8 9-11 3/8 103 3/4			<p>OTHER GRILLE PATTERNS</p> <div style="display: flex; justify-content: space-around; align-items: flex-end;"> <div style="text-align: center;"> PRAIRIE</div> <div style="text-align: center;"> DIAMOND</div> <div style="text-align: center;"> SINGLE PLAZA</div> <div style="text-align: center;"> DOUBLE PLAZA</div> <div style="text-align: center;"> TRIPLE PLAZA</div> </div>		
32100	64100				

* BOTTOM RAIL
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 1 3/8" FROM FRAME & ROUGH OPENING HEIGHTS.

OTHER PANEL OPTIONS

1/2 LITE PANEL	3/4 LITE PANEL	1/2 DIVIDED PANEL	3/4 DIVIDED PANEL

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"


Mas. Opg. Clad
Rough Opg.
Frame
* Glass

10-3 7/16
10-3 7/16
10-2 11/16
14 - 27 1/2 - 14


11-3 7/16
11-3 7/16
11-2 11/16
20 - 27 1/2 - 20

11-7 7/16
11-7 7/16
11-6 11/16
22 - 27 1/2 - 22


6-8
6-8
6-7 1/2
63 7/8



20-64-2068




26-64-2668




28-64-2868


6-10 7/8
6-10 7/8
6-10 3/8
66 3/4



20-64-20610




26-64-26610




28-64-28610


7-11 7/8
7-11 7/8
7-11 3/8
79 3/4



20-64-2080



26-64-2680



28-64-2880

* BOTTOM RAIL
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD


- ▣ ADD 2 13/16" TO FRAME WIDTH
- ▣ ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ▣ ADD 6 1/2" TO FRAME WIDTH
- ▣ ADD 3 1/4" TO FRAME HEIGHT


NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

OTHER GRILLE PATTERNS



PRAIRIE DIAMOND SINGLE PLAZA DOUBLE PLAZA TRIPLE PLAZA

OTHER PANEL OPTIONS



1/2 LITE PANEL 3/4 LITE PANEL 1/2 LITE DIVIDED PANEL 3/4 LITE DIVIDED PANEL

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 1 3/8" FROM FRAME & ROUGH OPENING HEIGHTS.







NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"


	Mas. Opg. Clad	3-7	7-0 13/16
	Rough Opg.	3-7	7-0 13/16
	Frame	3-6 1/4	7-0 1/16
	* Glass	32	32
6-8			
6-8			
6-7 1/2			
63 7/8			
		3668	7068
6-10 7/8			
6-10 7/8			
6-10 3/8			
66 3/4			
		36610	70610
7-11 7/8			
7-11 7/8			
7-11 3/8			
79 3/4			
		3680	7080

NOTE:
 THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 1 3/8" FROM FRAME & ROUGH OPENING HEIGHTS.

* BOTTOM RAIL
 FOR 5" ADD 3 3/8" TO GLASS HEIGHT
 FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

OTHER GRILLE PATTERNS



UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD


- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 1/4" TO FRAME HEIGHT

NOTE:
 ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

OTHER PANEL OPTIONS



















NOTES:
 CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
 ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING SIDELITES

ELEVATIONS

SCALE: 1/8" = 1'-0"

	1-3	1-5	1-7	2-1 1/4
Mas. Opg. Clad	1-3	1-5	1-7	2-1 1/4
Rough Opg.	1-2	1-4	1-6	2-0 1/4
Frame	7 1/2	9 1/2	11 1/2	14
* Glass				
6-8				
6-8				
6-7 1/2				
63 7/8	1268	1468	1668	2068
6-11				
6-11				
6-10 1/2				
66 3/4	12610	14610	16610	20610
8-0				
8-0				
7-11 3/8				
79 3/4	1280	1480	1680	2080
9-0				
9-0				
8-11 3/8				
91 3/4	1290	1490	1690	2090

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING


* BOTTOM RAIL
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

Pinnacle Series


CLAD PATIO DOOR - FRENCH INSWING

HANDING CONFIGURATIONS (ALL HANDINGS ARE VIEWED FROM THE EXTERIOR)





SINGLE DOOR





THREE UNIT DOOR






DOUBLE UNIT DOOR



BI-HINGE DOOR



FOUR UNIT DOOR




FLANKER UNITS MUST BE STATIONARY FOR QUAD HANDINGS

Pinnacle Series


CLAD PATIO DOOR - FRENCH INSWING

SCREEN OPTIONS


SLIDING SCREEN OPTION




X-O⁺




O-X⁺




X-O-O⁺




O-O-X⁺




O-X-O⁺



O-O-X-O⁺




O-X-O-O⁺




O-XO-O⁺


NO SCREEN OPTION




XR




XO




O-XO



XL



OX



XO-O

+ Standard handing configurations as shown are continuous head and sill.

Pinnacle Series

CLAD INSWING PATIO DOOR - IN-SASH TRANSOMS

ELEVATIONS

SCALE: 1/8" = 1'-0"

	Mas. Opg. Clad					
		2-7	5-0 13/16	5-0 13/16	7-6 5/8	7-6 5/8
		2-7	5-0 13/16	5-0 13/16	7-6 5/8	7-6 5/8
		2-6 1/4	5-0 1/16	5-0 1/16	7-5 7/8	7-5 7/8
		20	49 13/16	20	20	79 5/8
1-4 1/2	1-1 1/2	2611	5011	5011-2	7611-3	
1-4 1/2	1-4 1/2	2614	5014	5014-2	7614-3	7614
2-0 1/2	2-0 1/2	2620	5020	5020-2	7620-3	7620
		2-9	5-4 13/16	5-4 13/16	8-0 5/8	8-0 5/8
		2-9	5-4 13/16	5-4 13/16	8-0 5/8	8-0 5/8
		2-8 1/4	5-4 1/16	5-4 1/16	7-11 7/8	7-11 7/8
		22	53 13/16	22	22	85 5/8
1-4 1/2	1-1 1/2	2811	5411	5411-2	8011-3	
1-4 1/2	1-4 1/2	2814	5414	5414-2	8014-3	8014
2-0 1/2	2-0 1/2	2820	5420	5420-2	8020-3	8020
		3-1	6-0 13/16	6-0 13/16	9-0 5/8	9-0 5/8
		3-1	6-0 13/16	6-0 13/16	9-0 5/8	9-0 5/8
		3-0 1/4	6-0 1/16	6-0 1/16	8-11 7/8	8-11 7/8
		26	61 13/16	26	26	97 5/8
1-4 1/2	1-1 1/2	3011	6011	6011-2	9011-3	
1-4 1/2	1-4 1/2	3014	6014	6014-2	9014-3	9014
2-0 1/2	2-0 1/2	3020	6020	6020-2	9020-3	9020
		3-2 1/2	6-3 13/16	6-3 13/16	3-7	7-0 13/16
		3-2 1/2	6-3 13/16	6-3 13/16	3-7	7-0 13/16
		3-1 3/4	6-3 1/16	6-3 1/16	3-6 1/4	7-0 1/16
		28	65 13/16	28	32	73 13/16
1-4 1/2	1-1 1/2	3211	6411	6411-2	3611	7011
1-4 1/2	1-4 1/2	3214	6414	6414-2	3614	7014
2-0 1/2	2-0 1/2	3220	6420	6420-2	3620	7020

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 1/4" TO FRAME HEIGHT

NOTE:

ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

NOTES:

CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING


Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING


GRILLE PANELS FOR PANEL DOORS

SCALE: 1/8" = 1'-0"

3/4 LITE



PANEL HEIGHT & MIDRAIL LOCATIONS



NOTES:
HORIZONTAL GRILLE BARS WILL ONLY ALIGN WITH SIMILAR PANELS OR SIDE PANELS


Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING


GRILLE PANELS FOR PANEL DOORS

SCALE: 1/8" = 1'-0"

1/2 LITE



PANEL HEIGHT & MIDRAIL LOCATIONS



NOTES:
HORIZONTAL GRILLE BARS WILL ONLY ALIGN WITH SIMILAR PANELS OR SIDE PANELS

Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING


ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opq. Clad
Rough Opq.
Frame
* Glass


4-0 9/16
4-0 9/16
4-0 1/16
14

6-7 1/2
6-7 1/2
6-7
63 7/8




4068
BI-HINGE ONLY

6-10 3/8
6-10 3/8
6-9 7/8
66 3/4




40610
BI-HINGE ONLY

7-11 3/8
7-11 3/8
7-10 7/8
79 3/4




4080
BI-HINGE ONLY

8-11 3/8
8-11 3/8
8-10 7/8
91 3/4




4090
BI-HINGE ONLY

9-11 3/8
9-11 3/8
9-10 7/8
103 3/4




40100
BI-HINGE ONLY

OTHER GRILLE PATTERNS



OTHER PANEL OPTIONS



NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 7/8" FROM FRAME & ROUGH OPENING HEIGHTS.

* BOTTOM RAIL
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

UNIT SIZE INFORMATION

- FOR CLAD BRICKMOULD
- ▣ ADD 2 13/16" TO FRAME WIDTH
 - ▣ ADD 1 13/32" TO FRAME HEIGHT
- FOR CLAD WILLIAMSBURG
- ▣ ADD 6 1/2" TO FRAME WIDTH
 - ▣ ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series






CLAD PATIO DOOR - FRENCH OUTSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mass. Opp. Clad
Rough Opp.
Frame
*Glass

2-7	5-0 13/16	7-6 5/8	8-0 1/16	9-0 9/16	10-0 9/16
2-7	5-0 13/16	7-6 5/8	8-0 1/16	9-0 9/16	10-0 9/16
2-6 1/4	5-0 1/16	7-5 7/8	7-11 5/16	8-11 13/16	9-11 13/16
20	20	20	11 1/2 - 20 - 11 1/2	14 - 20 - 14	20




NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 7/8" FROM FRAME & ROUGH OPENING HEIGHTS.

* BOTTOM RAIL
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

OTHER GRILLE PATTERNS




UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
 ADD 2 13/16" TO FRAME WIDTH
 ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG
 ADD 6 1/2" TO FRAME WIDTH
 ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

OTHER PANEL OPTIONS



NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME


Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING


ELEVATIONS

SCALE: 1/8" = 1'-0"


Mass. Opg. Clad
Rough Opg.
Frame
* Glass




6-7 1/2
6-7 1/2
6-7
63 7/8




6-10 3/8
6-10 3/8
6-9 7/8
66 3/4



7-11 3/8
7-11 3/8
7-10 7/8
79 3/4



8-11 3/8
8-11 3/8
8-10 7/8
91 3/4




9-11 3/8
9-11 3/8
9-10 7/8
103 3/4

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 7/8" FROM FRAME & ROUGH OPENING HEIGHTS.

* BOTTOM RAIL
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

OTHER GRILLE PATTERNS




UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
 ADD 2 13/16" TO FRAME WIDTH
 ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG
 ADD 6 1/2" TO FRAME WIDTH
 ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

OTHER PANEL OPTIONS



NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opg. Clad
Rough Opg.
Frame
*Glass


	3-1	6-0 13/16	9-0 5/8	8-4 1/16	8-8 1/16
	3-1	6-0 13/16	9-0 5/8	8-4 1/16	8-8 1/16
	3-0 1/4	6-0 1/16	8-11 7/8	8-3 5/16	8-7 5/16
	26	26	26	7 1/2 - 26 - 7 1/2	9 1/2 - 26 - 9 1/2
6-7 1/2					
6-7 1/2	3068	6068	9068	12-60-1268	14-60-1468
6-10 3/8					
6-10 3/8	30610	60610	90610	12-60-12610	14-60-14610
6-9 7/8					
66 3/4					
7-11 3/8					
7-11 3/8	3080	6080	9080	12-60-1280	14-60-1480
7-10 7/8					
79 3/4					
8-11 3/8					
8-11 3/8	3090	6090			
8-10 7/8					
91 3/4					
9-11 3/8					
9-11 3/8	30100	60100			
9-10 7/8					
103 3/4					

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 7/8" FROM FRAME & ROUGH OPENING HEIGHTS.

* BOTTOM RAIL
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

OTHER GRILLE PATTERNS




UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
 ■ ADD 2 13/16" TO FRAME WIDTH
 ■ ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG
 ■ ADD 6 1/2" TO FRAME WIDTH
 ■ ADD 3 1/4" TO FRAME HEIGHT

OTHER PANEL OPTIONS



NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING


ELEVATIONS

SCALE: 1/8" = 1'-0"


Mas. Opg. Clad
Rough Opg.
Frame
*Glass

9-0 1/16	10-0 9/16	11-0 9/16	11-4 9/16
9-0 1/16	10-0 9/16	11-0 9/16	11-4 9/16
8-11 5/16	9-11 13/16	10-11 13/16	11-3 13/16
11 1/2 - 26 - 11 1/2	14 - 26 - 14	20 - 26 - 20	22 - 26 - 22


6-7 1/2
6-7 1/2
6-7
63 7/8



6-10 3/8
6-10 3/8
6-9 7/8
66 3/4



7-11 3/8
7-11 3/8
7-10 7/8
79 3/4




* BOTTOM RAIL
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 7/8" FROM FRAME & ROUGH OPENING HEIGHTS.

OTHER GRILLE PATTERNS




UNIT SIZE INFORMATION

- FOR CLAD BRICKMOULD
- ▣ ADD 2 13/16" TO FRAME WIDTH
 - ▣ ADD 1 13/32" TO FRAME HEIGHT
- FOR CLAD WILLIAMSBURG
- ▣ ADD 6 1/2" TO FRAME WIDTH
 - ▣ ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

OTHER PANEL OPTIONS



NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING


ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opg. Clad
Rough Opg.
Frame
* Glass


12-0 9/16
12-0 9/16
11-11 13/16
26

6-7 1/2
6-7 1/2
6-7
63 7/8




30-60-3068

6-10 3/8
6-10 3/8
6-9 7/8
66 3/4



30-60-30610

7-11 3/8
7-11 3/8
7-10 7/8
79 3/4



30-60-3080

* BOTTOM RAIL
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 7/8" FROM FRAME & ROUGH OPENING HEIGHTS.

OTHER GRILLE PATTERNS




PRAIRIE




DIAMOND



SINGLE PLAZA



DOUBLE PLAZA



TRIPLE PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD


- ▣ ADD 2 13/16" TO FRAME WIDTH
- ▣ ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG


- ▣ ADD 6 1/2" TO FRAME WIDTH
- ▣ ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING


OTHER PANEL OPTIONS




1/2 LITE
PANEL



3/4 LITE
PANEL



1/2 LITE
DIVIDED PANEL



3/4 LITE
DIVIDED PANEL

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING

ELEVATIONS


SCALE: 1/8" = 1'-0"

Masonry Opening Clad Frame Glass	3-2 1/2	6-3 13/16	8-7 1/16	8-11 1/16	9-3 1/16
	3-2 1/2	6-3 13/16	8-7 1/16	8-11 1/16	9-3 1/16
	3-1 3/4	6-3 1/16	8-6 5/16	8-10 5/16	9-2 5/16
	27 1/2	27 1/2	7 1/2 - 27 1/2 - 7 1/2	9 1/2 - 27 1/2 - 9 1/2	11 1/2 - 27 1/2 - 11 1/2
6-7 1/2 6-7 1/2 6-7 63 7/8					
	3268	6468	12-64-1268	14-64-1468	16-64-1668
6-10 3/8 6-10 3/8 6-9 7/8 66 3/4					
	32610	64610	12-64-12610	14-64-14610	16-64-16610
7-11 3/8 7-11 3/8 7-10 7/8 79 3/4					
	3280	6480	12-64-1280	14-64-1480	16-64-1680
8-11 3/8 8-11 3/8 8-10 7/8 91 3/4					
	3290	6490			
9-11 3/8 9-11 3/8 9-10 7/8 103 3/4					
	32100	64100			

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 7/8" FROM FRAME & ROUGH OPENING HEIGHTS.

* BOTTOM RAIL
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT




UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 1/4" TO FRAME HEIGHT



NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"


Mas. Opp. Clad
Rough Opp.
Frame
* Glass

10-3 9/16
10-3 9/16
10-2 13/16
14 - 27 1/2 - 14


11-3 9/16
11-3 9/16
11-2 13/16
20 - 27 1/2 - 20

11-7 9/16
11-7 9/16
11-6 13/16
22 - 27 1/2 - 22


6-7 1/2
6-7 1/2
6-7
63 7/8



20-64-2068




26-64-2668




28-64-2868


6-10 3/8
6-10 3/8
6-9 7/8
66 3/4



20-64-20610




26-64-26610




28-64-28610


7-11 3/8
7-11 3/8
7-10 7/8
79 3/4



20-64-2080



26-64-2680



28-64-2880

* **BOTTOM RAIL**
FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 7/8" FROM FRAME & ROUGH OPENING HEIGHTS.

OTHER GRILLE PATTERNS




PRAIRIE




DIAMOND



SINGLE PLAZA



DOUBLE PLAZA



TRIPLE PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD


- ▣ ADD 2 13/16" TO FRAME WIDTH
- ▣ ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG


- ▣ ADD 6 1/2" TO FRAME WIDTH
- ▣ ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING


OTHER PANEL OPTIONS




1/2 LITE
PANEL



3/4 LITE
PANEL



1/2 LITE
DIVIDED PANEL



3/4 LITE
DIVIDED PANEL







NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"


Mas. Opg. Clad Rough Opg. Frame *Glass	3-7	7-0 13/16
	3-7	7-0 13/16
	3-6 1/4	7-0 1/16
	32	32
6-7 1/2		
6-7 1/2	3668	7068
6-7 1/2	63 7/8	
6-10 3/8		
6-10 3/8	36610	70610
6-10 3/8	66 3/4	
6-9 7/8		
66 3/4		
7-11 3/8		
7-11 3/8	3680	7080
7-11 3/8	79 3/4	
7-10 7/8		
79 3/4		

NOTE:
 THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 7/8" FROM FRAME & ROUGH OPENING HEIGHTS.

* BOTTOM RAIL
 FOR 5" ADD 3 3/8" TO GLASS HEIGHT
 FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

OTHER GRILLE PATTERNS




PRAIRIE DIAMOND SINGLE PLAZA DOUBLE PLAZA TRIPLE PLAZA

UNIT SIZE INFORMATION

- FOR CLAD BRICKMOULD**
- ▣ ADD 2 13/16" TO FRAME WIDTH
 - ▣ ADD 1 13/32" TO FRAME HEIGHT
- FOR CLAD WILLIAMSBURG**
- ▣ ADD 6 1/2" TO FRAME WIDTH
 - ▣ ADD 3 1/4" TO FRAME HEIGHT

OTHER PANEL OPTIONS



1/2 LITE PANEL 3/4 LITE PANEL 1/2 LITE DIVIDED PANEL 3/4 LITE DIVIDED PANEL

NOTE:
 ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING





















NOTES:
 CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
 ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING SIDELITES

ELEVATIONS

SCALE: 1/8" = 1'-0"

	1-3	1-5	1-7	2-1 1/4
Mas. Opg. Clad	1-3	1-5	1-7	2-1 1/4
Rough Opg.	1-2	1-4	1-6	2-0 1/4
Frame	7 1/2	9 1/2	11 1/2	14
* Glass				
6-7 1/2				
6-7 1/2	1268	1468	1668	2068
6-7				
63 7/8				
6-10 1/2	12610	14610	16610	20610
6-10 1/2				
6-9 7/8				
66 3/4				
7-11 1/2	1280	1480	1680	2080
7-11 1/2				
7-10 7/8				
79 3/4				
8-11 1/2	1290	1490	1690	2090
8-11 1/2				
8-10 7/8				
91 3/4				

NOTES:

CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING

* BOTTOM RAIL

FOR 5" ADD 3 3/8" TO GLASS HEIGHT

FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Oppg. Clad
Rough Oppg.
Frame
* Glass

3-2 1/2
3-2 1/2
3-1 3/4
27 1/2

6-2 3/4
6-2 3/4
6-2
27 1/2


Mas. Oppg. Clad
Rough Oppg.
Frame
Glass

6-2 3/4
6-2 3/4
6-2
63 3/4


6-2 3/4
6-2 3/4
6-2
27 1/2

DOORS

6-6 5/8
6-6 5/8
6-6 1/8
63 7/8




3268-A




6468-A

6-9 1/2
6-9 1/2
6-9
66 3/4




32610-A




64610-A

7-10 1/2
7-10 1/2
7-10
79 3/4




3280-A




6480-A

8-10 1/2
8-10 1/2
8-10
91 3/4




3290-A




6490-A

9-10 1/2
9-10 1/2
9-10
103 3/4



32100-A



64100-A

IN-SASH TRANSOMS

1-1 1/2
1-1 1/2
1-1
6 1/2



6411-A




6411-2-A

1-4 1/2
1-4 1/2
1-4
9 1/2




6414-A




6414-2-A

2-0 1/2
2-0 1/2
2-0
17 1/2




6420-A



6420-2-A


OTHER GRILLE PATTERNS



PRAIRIE




DIAMOND



SINGLE PLAZA




DOUBLE PLAZA




TRIPLE PLAZA


OTHER PANEL OPTIONS




1/2 LITE PANEL



3/4 LITE PANEL



1/2 LITE DIVIDED PANEL



3/4 LITE DIVIDED PANEL

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ▣ ADD 2 13/16" TO FRAME WIDTH
- ▣ ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ▣ ADD 6 1/2" TO FRAME WIDTH
- ▣ ADD 3 1/4" TO FRAME HEIGHT

NOTE:

ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

* BOTTOM RAIL

FOR 5" ADD 3 3/8" TO GLASS HEIGHT
FOR 10" SUBTRACT 2" FROM GLASS HEIGHT

NOTES:

ADA DOORS INCLUDE / REQUIRE 10" BOTTOM RAIL, 3-2 PANEL & HANDICAP SILL
ADA DOORS ARE NOT RATED
ADA DOORS COME WITH NO BORE & NO HARDWARE
BI-HINGE DOORS DO NOT HAVE AN ASTRAGAL


CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series


CLAD PATIO DOOR - FRENCH OUTSWING

HANDING CONFIGURATIONS (ALL HANDINGS ARE VIEWED FROM THE EXTERIOR)





SINGLE DOOR





THREE UNIT DOOR






DOUBLE UNIT DOOR



BI-HINGE DOOR



FOUR UNIT DOOR



FLANKER UNITS MUST BE STATIONARY FOR QUAD HANDINGS

Pinnacle Series

CLAD OUTSWING PATIO DOOR - IN-SASH TRANSOMS

ELEVATIONS

SCALE: 1/8" = 1'-0"

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ▣ ADD 2 13/16" TO FRAME WIDTH
- ▣ ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ▣ ADD 6 1/2" TO FRAME WIDTH
- ▣ ADD 3 1/4" TO FRAME HEIGHT

NOTE:

ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

Mas. Opg. Clad Rough Opg. Frame Glass	2-7	5-0 13/16	5-0 13/16	7-6 5/8	7-6 5/8
	2-7	5-0 13/16	5-0 13/16	7-6 5/8	7-6 5/8
	2-6 1/4	5-0 1/16	5-0 1/16	7-5 7/8	7-5 7/8
	20	49 13/16	20	20	79 5/8
1-1 1/2					
1-4 1/2					
2-0 1/2					
2-0 1/2	2-9	5-4 13/16	5-4 13/16	8-0 5/8	8-0 5/8
2-0 1/2	2-9	5-4 13/16	5-4 13/16	8-0 5/8	8-0 5/8
2-0 1/2	2-8 1/4	5-4 1/16	5-4 1/16	7-11 7/8	7-11 7/8
2-0 1/2	22	53 13/16	22	22	85 5/8
1-1 1/2					
1-4 1/2					
2-0 1/2					
2-0 1/2	3-1	6-0 13/16	6-0 13/16	9-0 5/8	9-0 5/8
2-0 1/2	3-1	6-0 13/16	6-0 13/16	9-0 5/8	9-0 5/8
2-0 1/2	3-0 1/4	6-0 1/16	6-0 1/16	8-11 7/8	8-11 7/8
2-0 1/2	26	61 13/16	26	26	97 5/8
1-1 1/2					
1-4 1/2					
2-0 1/2					
2-0 1/2	3-2 1/2	6-3 13/16	6-3 13/16	3-7	7-0 13/16
2-0 1/2	3-2 1/2	6-3 13/16	6-3 13/16	3-7	7-0 13/16
2-0 1/2	3-1 3/4	6-3 1/16	6-3 1/16	3-6 1/4	7-0 1/16
2-0 1/2	28	65 13/16	28	32	73 13/16
1-1 1/2					
1-4 1/2					
2-0 1/2					
2-0 1/2					
2-0 1/2					
2-0 1/2					
2-0 1/2					

NOTES:

CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING


Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING


GRILLE PANELS FOR PANEL DOORS

SCALE: 1/8" = 1'-0"

3/4 LITE



PANEL HEIGHT & MIDRAIL LOCATIONS



NOTES:
HORIZONTAL GRILLE BARS WILL ONLY ALIGN WITH SIMILAR PANELS OR SIDE PANELS


Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING


GRILLE PANELS FOR PANEL DOORS

SCALE: 1/8" = 1'-0"

1/2 LITE



PANEL HEIGHT & MIDRAIL LOCATIONS



NOTES:
HORIZONTAL GRILLE BARS WILL ONLY ALIGN WITH SIMILAR PANELS OR SIDE PANELS