



Windsor Windows and Doors

Next Dimension Performance Ratings

Series	Window Type	Operator Type	Performance Option	Tested Callout	Tested Frm Width (in)	Tested Frm Height (in)	PG Rating	+DP (psf)	-DP (psf)	+STP (psf)	-STP (psf)	Water (psf)	Air (cfm/ft ²)	V _{asd} (MPH)	V _{ult} (MPH)
New Next Dimension	Awning	Crank-Out	Standard	4836	47.5	35.5	LC-PG50-AP	50	50	75	75	7.50	0.10	140	180
	Casement	Crank-Out	Standard	3672 3-lock	35.5	71.5	LC-PG50-C	50	50	75	75	7.50	0.09	140	180
	Casement	Fixed	Standard	9672	95.5	71.5	CW-PG50-FW	50	50	75	75	7.50	0.03	140	180
	Single Hung		Standard	3672	35.5	71.5	LC-PG50-H	50	50	75	75	7.50	0.13	140	180
	Single Hung		Standard	5484	53.5	83.5	LC-PG50-H	50	50	75	75	7.50	0.09	140	180
	2-Wide Single Hung		Standard	5484-2	107.5	83.5	LC-PG35-H	35	35	52.5	52.5	5.25	0.10	117	151
	3-Wide Single Hung		Standard	3672-3	107.5	71.5	LC-PG50-H	50	50	75	75	7.50	0.20	140	180
	3-Wide Single Hung		Standard	3684-3	107.5	83.5	LC-PG50-H	50	50	75	75	7.50	0.07	140	180
	Double Hung		Standard	4884	47.5	83.5	LC-PG50-H	50	50	75	75	7.50	0.10	140	180
	2-Wide Double Hung		Standard	4884-2	95.5	83.5	LC-PG50-H	50	50	75	75	7.50	0.13	140	180
	3-Wide Double Hung		Standard	3672-3	107.5	71.5	LC-PG50-H	50	50	75	75	7.50	0.20	140	180
	3-Wide Double Hung		Standard	3684-3	107.5	83.5	LC-PG50-H	50	50	75	75	7.50	0.19	140	180
	Sliding Window		Standard	7272	71.5	71.5	LC-PG50-HS	50	50	75	75	7.50	0.08	140	180
	Sliding Window	End Vent	Standard	24-48-2472	95.5	71.5	LC-PG35-HS	35	35	52.5	52.5	5.25	0.07	117	151
	Sliding Window	End Vent	Standard	24-48-2454	95.5	53.5	LC-PG50-HS	50	50	75	75	7.50	0.07	140	180
	SH/DH Fixed	Picture	Standard	9660	95.5	59.5	CW-PG50-FW	50	50	75	75	7.50	0.01	140	180
	SH/DH Fixed	Picture	Standard	7272	71.5	71.5	CW-PG50-FW	50	50	75	75	7.50	0.01	140	180
	Direct Set / Radius	Fixed	Standard	9672	95.5	71.5	CW-PG50-FW	50	50	75	75	7.50	0.03	140	180
	Direct Set / Radius	Fixed	Standard	7272	71.5	71.5	CW-PG50-FW	50	50	75	75	7.50	0.03	140	180
	Narrow Sliding Door	Sidelite	Standard	4080	47.5	95.5	LC-PG35-FD	35	35	52.5	52.5	5.25	0.07	117	151
	Narrow Sliding Door	2 Panel	Standard	8080	95.5	95.5	LC-PG35-SD	35	35	52.5	52.5	5.25	0.19	117	151
	Narrow Sliding Door	3 Panel	Standard	9080	107.5	95.5	LC-PG35-SD	35	35	52.5	52.5	5.25	0.19	117	151
	Narrow Sliding Door	Quad	Standard	12Q80	140.875	95.5	LC-PG25-SD	25	25	37.5	37.5	3.75	0.20	99	128
	Narrow Door Transom	Transom	Standard	108 x 24	108	24	LC-PG35-TR	35	35	52.5	52.5	5.25	0.03	117	151
	HP French Sliding Door	Sidelite	Standard	4080	47.5	95.5	LC-PG50-FD	50	50	75	75	7.50	0.02	140	180
	HP French Sliding Door	2 Panel	Standard	8080	95.5	95.5	LC-PG50-SD	50	50	75	75	7.50	0.12	140	180
	HP French Sliding Door	3 Panel	Standard	9080	108	95.5	LC-PG50-SD	50	50	75	75	7.50	0.13	140	180
	HP French Sliding Door	Quad	Standard	12Q80	143.5	95.5	LC-PG50-SD	50	50	75	75	7.50	0.20	140	180

DP = Design Pressure
STP = Structural Test Pressure

V_{asd} = Nominal Design Wind Speed
V_{ult} = Ultimate Design Wind Speed