



Windsor Windows and Doors

Next Dimension Classic, Pro, Signature Performance Ratings

Series	Window Type	Operator Type	Performance Option	Tested Callout	Tested Frm Width (in)	Tested Frm Height (in)	PG Rating	+DP (psf)	-DP (psf)	+STP (psf)	-STP (psf)	Water (psf)	V _{asd} (MPH)	V _{ult} (MPH)
Next Dimension Classic Brickmould	2-Wide Double Hung		Standard	3666-2	72	66	R-PG40-H	40	40	60	60	6.00	125	161
	2-Wide Double Hung		Standard	4884-2	96	84	LC-PG30-H	30	30	45	45	4.50	108	140
	2-Wide Double Hung		DP Upgrade	3672-2	72	72	LC-PG45-H	45	45	68	68	6.75	133	171
	2-Wide Single Hung		Standard	3662-2	72	62	R-PG45-H	45	45	68	68	6.75	133	171
	2-Wide Single Hung		Standard	4884-2	96	84	R-PG35-H	35	35	53	53	5.25	117	151
	3-Wide Double Hung		Standard	3684-3	108	84	R-PG30-H	30	30	45	45	4.50	108	140
	3-Wide Single Hung		Standard	3684-3	108	84	R-PG35-H	35	35	53	53	5.25	117	151
	Double Hung		Standard	3666-1	36	66	R-PG40-H	40	40	60	60	6.00	125	161
	Double Hung		Standard	4884-1	48	84	LC-PG30-H	30	30	45	45	4.50	108	140
	Double Hung		DP Upgrade	3672-1	36	72	R-PG50-H	50	50	75	75	7.50	140	180
	Double Hung	Picture	Standard	9648	96	48	R-PG50-FW	50	50	75	75	7.50	140	180
	Double Hung	Picture	Standard	9661	96	60	LC-PG40-FW	40	40	60	60	6.00	125	161
	Single Hung		Standard	3672-1	36	72	R-PG50-H	50	50	75	75	7.50	140	180
	Single Hung		Standard	4884-1	48	84	LC-PG40-H	40	40	60	60	6.00	125	161
	Single Hung	Picture	Standard	9661	96	61	LC-PG50-FW	50	50	75	75	7.50	140	180
	Sliding Window		Standard	6060	60	60	R-PG35-HS	35	35	53	53	5.25	117	151
	Sliding Window	End-Vent	Standard	24-48-2460	96	60	R-PG30-HS	30	30	45	45	4.50	108	140
	Sliding Window		Standard	7272	72	72	R-PG20-HS	20	20	30	30	3.00	88	114
Sliding Window	End-Vent	Standard	24-48-2472	96	72	R-PG20-HS	20	20	30	30	3.00	88	114	
Next Dimension Classic Standard	2-Wide Double Hung		Standard	4884-2	96	84	LC-PG30-H	30	30	45	45	4.50	108	140
	2-Wide Double Hung		DP Upgrade	3672-2	72	72	R-PG45-H	45	45	68	68	6.75	133	171
	3-Wide Double Hung		Standard	3684-3	108	84	LC-PG35-H	35	35	53	53	5.25	117	151
	Double Hung	Picture	Standard	9661	96	61	CW-PG50-FW	50	50	75	75	7.50	140	180
	Double Hung		Standard	3666-1	36	66	LC-PG40-H	40	40	60	60	6.00	125	161
	Double Hung		Standard	4884-1	48	84	LC-PG30-H	30	30	45	45	4.50	108	140
Double Hung		DP Upgrade	3672-1	36	72	LC-PG50-H	50	50	75	75	7.50	140	180	
Next Dimension Pro Brickmould	Direct Set / Radius		Standard	96 x 60	96	60	R-PG35-FW	35	35	53	53	5.25	117	151
	Direct Set / Radius		Standard	72 x 78	72	78	CW-PG35-FW	35	35	53	53	5.25	117	151
	Single Hung		Standard	4578-1 2-lock	45	78	LC-PG40-H	40	40	60	60	6.00	125	161
	Single Hung		Standard	4884-1 2-lock	48	84	LC-PG35-H	35	35	53	53	5.25	117	151
	Single Hung		Standard	3618-3/3660-3	108	78	LC-PG35-H	35	35	53	53	5.25	117	151
	Single Hung		Standard	4278-2 2-lock	84	78	LC-PG30-H	30	30	45	45	4.50	108	140
	Single Hung		Standard	3678-3 1-lock	108	78	LC-PG30-H	30	30	45	45	4.50	108	140
	Single Hung		Standard	9024-1/3048-3	90	72	LC-PG30-H	30	30	45	45	4.50	108	140
	Sliding Window		Standard	6060 2-lock	60	60	LC-PG30-HS	30	30	45	45	4.50	108	140
	Sliding Window		Standard	7266 2-lock	72	66	LC-PG25-HS	25	25	38	38	3.75	99	128
	Sliding Window		Standard	9660/24-48-2424	96	84	R-PG25-HS	25	25	38	38	3.75	99	128
	Sliding Window		Standard	24-48-2466 2 lck	96	66	LC-PG25-HS	25	25	38	38	3.75	99	128



Windsor Windows and Doors

Next Dimension Classic, Pro, Signature Performance Ratings

Series	Window Type	Operator Type	Performance Option	Tested Callout	Tested Frm Width (in)	Tested Frm Height (in)	PG Rating	+DP (psf)	-DP (psf)	+STP (psf)	-STP (psf)	Water (psf)	V _{asd} (MPH)	V _{ult} (MPH)
Next Dimension Pro Standard	Direct Set / Radius		Standard	42 x 54	42	54	R-PG50-FW	50	50	75	75	7.50	140	180
	Direct Set / Radius		Standard	72 x 84	72	84	LC-PG35-FW	35	35	53	53	5.25	117	151
	Single Hung		Standard	3660-2 1 lock	72	60	R-PG40-H	40	40	60	60	6.00	125	161
	Single Hung		Standard	4578-1 2-lock	45	78	LC-PG35-H	35	35	53	53	5.25	117	151
	Single Hung		Standard	2424-2/2448-2	48	72	LC-PG35-H	35	35	53	53	5.25	117	151
	Single Hung		Standard	2460-3 1-lock	72	60	LC-PG35-H	35	35	53	53	5.25	117	151
	Single Hung		Standard	3024-3/3048-3	90	78	LC-PG35-H	35	35	53	53	5.25	117	151
	Single Hung		Standard	4884-1 2-lock	48	84	LC-PG30-H	30	30	45	45	4.50	108	140
	Single Hung		Standard	4278-2 2-lock	84	78	LC-PG30-H	30	30	45	45	4.50	108	140
	Single Hung		Standard	4218-2/4254-2	84	72	LC-PG30-H	30	30	45	45	4.50	108	140
	Single Hung		Standard	3678-3 1-lock	108	78	LC-PG30-H	30	30	45	45	4.50	108	140
	Single Hung		Standard	3618/3660-3	108	78	LC-PG30-H	30	30	45	45	4.50	108	140
	Single Hung		Standard	9024-1/3048-3	90	72	LC-PG30-H	30	30	45	45	4.50	108	140
	Sliding Window		Standard	6060 2-lock	60	60	R-PG30-HS	30	30	45	45	4.50	108	140
	Sliding Window		Standard	24-48-2460 2 lck	96	60	R-PG30-HS	30	30	45	45	4.50	108	140
	Sliding Window		Standard	7266 2-lock	72	66	LC-PG25-HS	25	25	38	38	3.75	99	128
Sliding Window		Standard	24-48-2466 2 lck	96	66	LC-PG25-HS	25	25	38	38	3.75	99	128	
Next Dimension Signature	Awning	Crank-Out	Standard	4830	48	30	R-PG50-AP	50	50	75	75	7.50	140	180
	Casement	Crank-Out	Standard	3672 3-lock	36	72	LC-PG50-C	50	50	75	75	7.50	140	180
	Casement	Fixed	Standard	3672	36	72	R-PG50-FW	50	50	75	75	7.50	140	180
	Casement	Fixed	Standard	9672	96	72	CW-PG30-FW	30	30	45	45	4.50	108	140
	Direct Set / Radius		Standard	72 x 72	72	72	CW-PG50-FW	50	50	75	75	7.50	140	180
	Direct Set / Radius		Standard	96 x 72	96	72	CW-PG40-FW	40	40	60	60	6.00	125	161
	Direct Set / Radius		Standard	8482	84	82	CW-PG40-FW	40	40	60	60	6.00	125	161
	Sliding Door	Narrow	Standard	4080 Stationary	48	96	CW-PG40-FD	40	40	60	60	6.00	125	161
	Sliding Door	Narrow	Standard	8080	96	96	LC-PG30-SD	30	30	45	45	4.50	108	140
	Sliding Door	Narrow	Standard	60610	72	82	R-PG30-SD	30	30	45	45	4.50	108	140
	Sliding Door	Narrow	DP Upgrade	60610	72	82	R-PG50-SD	50	50	75	75	7.50	140	180

DP = Design Pressure
STP = Structural Test Pressure

V_{asd} = Nominal Design Wind Speed
V_{ult} = Ultimate Design Wind Speed