

Pinnacle Select Doors

Model	Interior	Thermal Performance				Air/Water/Structural	
		LoE 366 / Argon		Dual LoE / Argon		Rating	Size
		U-Value	SHGC	U-Value	SHGC		
Select Bi-Fold	Aluminum	0.36	0.21	0.32	0.20	LC-PG-45 (1L-3R)	12'-8" x 10'-5"
						LC-PG-50 (2L-2R)	12'-8" x 10'-5"
						DP-15 (2L-2R) - Structural DP-30 (2L-2R) - Water	14'-9" x 12'-6"
Select Bi-Fold	Wood	0.36	0.21	0.32	0.20	DP-15 (2L-2R) - Structural DP-30 (2L-2R) - Water	14'-9" x 12'-6"
Select Multi-Slide	Aluminum	0.43	0.21	0.39	0.21	CW PG-30 (Lift and Slide)	12'-0 x 10'-3"
						LC PG-55 (Lift and Slide)	12'-0 x 10'-3"
						DP +25/-20 - Structural DP-30 - Water	19'-9" x 12'-2"
Select Multi-Slide	Wood	0.39	0.21	0.35	0.21	LC PG-40 (Lift and Slide)	12'-0 x 10'-3"
						DP +25/-20 - Structural DP-30 - Water	19'-9" x 12'-2"
Select Inswing	Aluminum	0.42	0.20	0.38	0.20	DP +35/-35 - Structural DP-25 - Water	7'-4" x 12'-3"
	Wood	0.42	0.20	0.38	0.20	DP +35/-35 - Structural DP-25 - Water	7'-4" x 12'-3"
Select Outswing	Aluminum	0.46	0.21	0.40	0.20	CW PG-60	3'-6" x 7'-2"
	Wood	0.46	0.21	0.40	0.20	DP +35/-35 - Structural DP-30 - Water	7'-4" x 12'-3"
Select Pivot Door	Aluminum	0.43	0.19	0.40	0.19	Not Tested	
	Wood	0.38	0.18	0.34	0.17		
	Voyage		N/A				DP +50/-50 - Structural DP-25 - Water