



# Windsor Windows and Doors

## Revive Performance Ratings

Series	Window Type	Operator Type	Performance Option	Tested Callout	Tested Frm Width (in)	Tested Frm Height (in)	PG Rating	+DP (psf)	-DP (psf)	+STP (psf)	-STP (psf)	Water (psf)	V <sub>asd</sub> (MPH)	V <sub>ult</sub> (MPH)
Revive Clad	Awning	Crank-Out	Standard	4432	48	36	R-PG40-AP	40	40	60	60	6.00	125	161
	Awning	Crank-Out	Standard	5656	60	60	R-PG30-AP	30	30	45	45	4.60	108	140
	Casement	Fixed	Standard	6880	72	84	R-PG45-FW	45	45	68	68	6.75	133	171
	Casement	Crank-Out	Standard	3856	42	60	R-PG40-C	40	40	60	60	6.00	125	161
	Casement	Crank-Out	Standard	3268	36	72	LC-PG30-C	30	30	45	45	4.60	108	140
	Casement	Crank-Out	Standard	2480	28	84	R-PG30-C	30	30	45	45	4.60	108	140
	Double Hung	Ez-Tilt	Standard	4244	47.375	96.75	LC-PG35-H	35	35	53	53	5.25	117	151
	Double Hung Picture	Picture	Standard	6870	49.375	96.75	LC-PG35-FW	35	35	53	53	5.25	117	151
	Double Hung Picture	Picture	Standard	6870	73.375	76.75	LC-PG35-FW	35	35	53	53	5.25	117	151
Revive HBR	Awning	Crank-Out	Standard	4432	48	36	R-PG35-AP	35	35	53	53	5.25	117	151
	Casement	Crank-Out	Standard	2474	28	78	LC-PG35-C	35	35	53	53	5.40	117	151
	Casement	Crank-Out	Standard	3268	36	72	LC-PG30-C	30	30	45	45	4.60	108	140
	Double Hung	Ez-Tilt	Standard	3636	41	80	LC-PG30-H	30	30	45	45	4.50	108	140
	Double Hung Picture	Picture	Standard	5668	61.375	76.75	LC-PG30-FW	30	30	45	45	4.50	108	140
	Casement	Fixed	Standard	6874	72	78	LC-PG40-FW	45	45	68	68	6.75	133	171

DP = Design Pressure  
STP = Structural Test Pressure

V<sub>asd</sub> = Nominal Design Wind Speed  
V<sub>ult</sub> = Ultimate Design Wind Speed